




Enapter

ELECTROLYSER 2.1 BATTERY LIMITS

DOCUMENT N°: ELE21-BLI-INT01


Rev.	Status	Date	Revision memo	Issued by	Checked by	Approved by
00	IFP	01/10/2020	Front panel change	K.El Sherbiny	C. Poggesi	J.J.Schmidt

This document is the property of Enapter S.r.l. and must not be copied or used for any purpose other than that for which it has been supplied. When printed it is considered as a for information only copy. The controlled copy is the screen version and it is the holder's responsibility that he/she holds the latest valid version.

	ELECTROLYSER 2.1 BATTERY LIMITS		Document number ELE21-BLI-INT02	
			Revision: 00	Status: IFP
	Discipline: PRO	Rev Date: 01/10/2020	Page 2 of 9	

INDEX

INDEX	2
1 PURPOSE	3
2 FIELD OF APPLICATION	3
3 DEFINITIONS AND ABBREVIATIONS	3
4 REFERENCE DOCUMENTS	3
5 RESPONSIBILITIES	3
6 ELECTROLYSER 2.1 INTERFACES	4
7 INTERFACE SPECIFICATIONS	5
7.1 H₂O IN	5
7.2 O₂ VENT	5
7.3 H₂ OUT	6
7.4 H₂ PURGE	6
7.5 FILL/DRAIN	7
7.6 POWER	7
7.7 DRY CONT.	8
7.8 ETH	8
8 APPENDIX: INTERFACE DRAWING ELE21-DRW-INT02-REV00	9

	ELECTROLYSER 2.1 BATTERY LIMITS		Document number ELE21-BLI-INT02	
			Revision: 00	Status: IFP
	Discipline: PRO	Rev Date: 01/10/2020	Page 3 of 9	

1 PURPOSE

The scope of this document is to define and describe the battery limits of the Electrolyser 2.1. It illustrates the physical interface ports of the Electrolyser, to allow its user to integrate it with the other equipment that composes his system.

2 FIELD OF APPLICATION

ELE210535A2AV03 & ELE210508A2AV03 only

3 DEFINITIONS AND ABBREVIATIONS

ELE21	Electrolyser 2.1
P&ID	Piping and Instrumentation Diagram
User	The integrator of the ELE21 in a larger system
Warranty	A written guarantee, issued to the purchaser of an ELE21 by Enapter, promising to repair or replace it as outlined in “Enapter’s Factory Warranty”

4 REFERENCE DOCUMENTS

Code	Name
ELE21-PID-000R1	Electrolyser 2.1 P&ID
ELE21-DRW-INT02	Electrolyser 2.1 Interfaces
ELE21-MAN-00002	Electrolyser 2.1 User Manual

5 RESPONSIBILITIES

User: It is the User’s responsibility to adhere to the ranges and constraints set henceforth. Failure to do so may cause the system to behave in an unpredictable/unsafe behaviour and render void the product Warranty.



ELECTROLYSER 2.1 BATTERY LIMITS

Document number
ELE21-BLI-INT02

Revision: 00

Status: IFP


Discipline: PRO


Rev Date: 01/10/2020

Page 4 of 9

6 ELECTROLYSER 2.1 INTERFACES

The following figure shows the positions of the ELE21 physical interfaces. All interfaces are located on the front panel.



	ELECTROLYSER 2.1 BATTERY LIMITS		Document number ELE21-BLI-INT02	
			Revision: 00	Status: IFP
	Discipline: PRO	Rev Date: 01/10/2020	Page 5 of 9	

7 INTERFACE SPECIFICATIONS

The values set in the following tables are operative values to be taken into account in the User system interface with ELE21.

7.1 H₂O IN

This inlet port is used for the automatic refilling of de-ionized water. At the back of this port is a solenoid valve that opens when refilling is needed.


Name	H ₂ O IN
Fitting Type	8 mm OD Pushfit female fitting
Fitting Material	LLDPE
Fluid	De-ionised water (<20 µS/cm)
Flowrate	0-4 L/min
Pressure	0,5-4 barg
Temperature	6-55°C

- Water is required to be supplied to the device from a pressurised source. If the pressure is higher than 4 bar, a warning appears on the ELE21. If the pressure is too low, refilling does not start. If pressure drops below 0.5 barg during refilling, the ELE21 issues a warning message.
- When water with a temperature lower than 6°C is detected, an error on the ELE21 is triggered. Water with a temperature higher than 58°C also triggers an error on the ELE21 and can damage the ELE21.
- The input water must, at all times, have a conductivity lower than 20 µS/cm. Failure to do this results in accelerated degradation of the stack and damages the system.
- Any plastic piping with an outside diameter of 8 mm is compatible with the interface fitting. Particular care should be taken in selecting material resistant to KOH corrosion.

7.2 O₂ VENT

This outlet port is directly connected to the electrolyte tank, and its primary function is to evacuate the produced O₂. Apart from O₂, a small quantity of H₂ (<2% concentration) and up to 25 mL/h of H₂O vapour is part of the effluent. It also serves as an overflow port if the ELE21 electrolyte tank is topped up with too much water due to a refilling malfunction.

Name	O ₂ VENT
Fitting Type	10 mm OD Pushfit female fitting
Fitting Material	LLDPE
Fluid	O ₂ + H ₂ O vapour+ H ₂ (<2%)
Flowrate	0-250 NL/h
Pressure	0-0,5 barg
Temperature	20-55°C

	ELECTROLYSER 2.1 BATTERY LIMITS		Document number ELE21-BLI-INT02	
			Revision: 00	Status: IFP
	Discipline: PRO	Rev Date: 01/10/2020	Page 6 of 9	

- No blockage or valves should be present on the User side of the interface. The port should be connected to a safe location open to atmosphere.
- The system is designed to withstand no more than 0,5 barg. An error on the ELE21 triggers if any overpressure is found on the line. Pressures exceeding 0,5 barg can damage the ELE21.
- The flow rate is proportional to the ELE21 H₂ production rate – i.e., at 50% of production capacity, 50% of the nominal oxygen flowrate exits the vent line.
- Any plastic piping with an outside diameter of 10 mm is compatible with the interface fitting. Particular care should be taken in selecting material resistant to KOH corrosion.

7.3 H₂ OUT

This outlet port is from which the Electrolyser produces Hydrogen. It is internally protected by a pressure control device and check valve to eliminate the possibility of gas backflow.

Name	H ₂ OUT
Fitting Type	¼" double ferrule female compression fitting (Swagelok)
Fitting Material	316L Stainless Steel
Fluid	H ₂
Flowrate	0-500 NL/h
Pressure	0-35 barg
Temperature	20-55°C


- Particular care should be taken not to attach any pressurised system with a pressure higher than 40 barg to the system.
- The outlet pressure is regulated by the User's downstream equipment. Operative pressure range should stay between 0 and 35 barg.
- The User should connect piping with compatible material – i.e. 316L Stainless Steel.

7.4 H₂ PURGE

This outlet port is from which the Electrolyser purges all internal hydrogen and accumulated water on the cathode side. A solenoid valve is used to release pressure.

Name	H ₂ PURGE
Fitting Type	¼" double ferrule female compression fitting (Swagelok)
Fitting Material	316L Stainless Steel
Fluid	H ₂ + LIQUID H ₂ O
Flowrate	0-35 NL/sec (transient)
Pressure	0-35 barg (transient)
Temperature	20-55°C

- No blockage or valves should be present on the User side of the interface as critical ELE21 safety measures are dependent on it. The port should be connected to a safe location open to atmosphere.
- The ELE21 purges twice during ramp-up, each of the purges occurring at 5 barg internal pressure. The ELE21 additionally purges every 24 hours, when User ramps the system down, or when – for any given

	ELECTROLYSER 2.1 BATTERY LIMITS		Document number ELE21-BLI-INT02	
			Revision: 00	Status: IFP
	Discipline: PRO	Rev Date: 01/10/2020	Page 7 of 9	

reason – the electrolyser needs to go into a safe state. The output from this port is not constant; it only occurs during production when any of the conditions above are met. During the purge, all the pressurised H₂ and water accumulated in the ELE21 internal water trap are expelled suddenly. A transient high-pressure flow is expected, whose characteristics are dependent on the User piping side of this interface.

- The User should connect piping with compatible material – i.e. 316L Stainless Steel.

7.5 FILL/DRAIN

This port is used only during the first refilling of electrolyte solution or during maintenance. This port is also used during draining of the ELE21 during maintenance. The connector needed to plug into this interface is provided by Enapter.

Name	FILL/DRAIN
Fitting Type	10 mm CPC female coupling
Fitting Material	POM (Polyoxymethylene)
Fluid	Aqueous KOH solution (1%-2% concentration)
Flowrate	0-1.6 L/min.
Pressure	Atmospheric
Temperature	6-55°C


- Enapter provides the male coupling and piping to connect to this port with the Electrolyte for first refilling. Any plastic piping with an outside diameter of 10 mm is compatible with the interface fitting. Particular care should be taken in selecting material resistant to KOH.

7.6 POWER

This inlet port is needed to provide power to the ELE21. The connector needed to plug into this interface is provided by Enapter.

Name	POWER
Fitting Type	PCB 3-pin 7,62 mm pitch female connector
Fitting Material	PA (polyamide)
Fluid	Electric current
Current	0-13 A
Voltage	220-240 V _{AC}
Frequency	50/60 Hz

- Enapter provides the male coupling to connect to this port. Conductors with a cross-section up to 4 mm² are compatible with the Enapter provided male coupling.

	ELECTROLYSER 2.1 BATTERY LIMITS		Document number ELE21-BLI-INT02	
			Revision: 00	Status: IFP
	Discipline: PRO	Rev Date: 01/10/2020	Page 8 of 9	

7.7 DRY CONT.

This plug is used for operating the integrated dry contact function. The connectors needed to plug into this interface are provided by Enapter.


Name	SAFETY
Fitting Type	PCB 4-pin 5,08 mm pitch female connector
Fitting Material	PA (polyamide)
Fluid	Electricity
Voltage	0-5 V _{DC}

- Enapter provides the male couplings to connect to this port. Conductors with a cross-section up to 2,5 mm² are compatible with the Enapter provided male couplings.


7.8 ETH

This inlet port allows the User access to the ELE21 Modbus control and monitoring.

Name	ETH
Fitting Type	Female Ethernet port

	ELECTROLYSER 2.1 BATTERY LIMITS		Document number ELE21-BLI-INT02	
			Revision: 00	Status: IFP
Discipline: PRO		Rev Date: 01/10/2020		Page 9 of 9

8 APPENDIX: INTERFACE DRAWING ELE21-DRW-INT02-REV00



ELECTROLYSER 2.1 INTERFACE LIST

#	NAME	TYPE	MATERIAL	FLUID	FLOWRATE	PRESSURE	TEMPERATURE
A	H ₂ O IN	8 mm OD John Guest Speedfit female fitting	LLDPE	De-ionised water	0-4 L/min	0,5-4 barg	6-55°C
B	O ₂ Vent	10 mm OD John Guest Speedfit female fitting	LLDPE	O ₂ + H ₂ O vapour + H ₂ (<2%)	0-250 NL/h	0-0,5 barg	20-55°C
C	H ₂ OUT	1/4" double ferrule female compression fitting	316L Stainless Steel	H ₂	0-500 NL/h	0-35 barg	20-55°C
D	H ₂ PURGE	1/4" double ferrule female compression fitting	316L Stainless Steel	H ₂ + liquid H ₂ O	0-35 L/s (transient)	0-35 bar (transient)	20-55°C
E	FILL / DRAIN	10 mm CPC female coupling	POM (Polyoxymethylene)	Aqueous KOH solution (1-2%)	0-1,62 L/min	Atmospheric	6-55°C
F	POWER	PCB 3-pin 7.62mm pitch female connector	PA (Polyamide)	Electric current	0-13 A / 200-240 V _{AC} / 50-60 Hz		
G	DRY CON.	PCB 4-pin 5.08mm pitch female connector	PA (Polyamide)	/	/	/	/
H	ETH	Ethernet port	/	/	/	/	/

All the information contained in this drawing is the sole property of Enapter and strictly confidential. Any reproduction in part or as a whole without the written permission of Enapter is prohibited.

DESIGN BY	L. Giobbi		
CHECKED	K. El Sherbiny		
APPROVED	J. J. Schmidt		
DISCIPLINE:	PJM	DATE:	01/10/2020
DRAWING STATUS:	IFI	SHEET:	1 of 1
		SCALE:	N/A
DRAWING TITLE:		ELE 2.1 INTERFACES	
DRAWING N-:		ELE21-DRW-INT02_rev00	

